

LARUE

Detachable snowblower



D45



Detachable snowblower

Performance¹

Capacity: up to 2,100 tons/hour
Casting distance: up to 46 m (150 ft.)

Dimensions²

Length from attach plate to front: 1,98 m (78 in.)
Overall width: 2,7 m (108 in.)
Overall height: 3,28 m (129 in.)
Working height: 1,35 m (53 in.)
Weight²: 3,624 kg (7,990 lb)

Engine

Various makes
Power: from 150 kW (202 hp) to 171 kW (230 hp)

Driveline system

Mechanical type equipped with clutch and protecting devices.

Hydraulic system

Pump: direct drive
Filter with replaceable cartridge
Valves electro-hydraulic type
Controlled by in-cab multifunctional joystick

Impeller

Easy replaceable blades
Heavy duty spoke type
Impeller casing made of steel (highly abrasive resistant)
Hydraulic impeller casing rotation

Conveyor

Type: Ribbon (serrated)
Diameter: 813 mm (32 in.)

Truck loading chute

Hydraulically controlled
Horizontal rotation angle: 300°
Casting distance: 1.2 m (4 ft.) to 15 m (50 ft.)
Telescopic section of 762 mm (30 in.) (optional)

Options

Female quick attach
Hydraulic steering vanes
Impeller casing having a 150° adjustable cast angle: Flat from the right to 30° to the left.
Carbide type: impeller casing, loading chute, scraper blade and/or skates
Residential type muffler
High resistance rubber scraper blade
Right side hydraulic tilting chute
Battery charger and/or battery heater
Trumpet horn
Telescopic loading chute
Wireless controls
Full skid width
LED lights

Notes:

1. Theoretical and depends on snow conditions.
2. Varies with options, measured without fuel.



Due to continuous improvement, the specifications and appearances in this brochure may change without prior notice.

For more information, please contact the manufacturer J.A. Larue Inc. or your local distributor.

Deposit brand 1999, all right reserved | Manufactured by: **J.A. Larue Inc.**
660, Lenoir, Québec (Québec) Canada G1X 3W3
Tel: **418-658-3003** | Toll free: 1-877-658-3013 | Fax: 418-658-6799
Web site: www.jalarue.com | E-mail: jalarue@jalarue.com

Your authorized distributor:

